

CHEMTRONICS

Technical Data Sheet

TDS CM502

Microtips™

PRODUCT DESCRIPTION

Chemtronics® **Microtips™** are designed for precision applications needing pinpoint accuracy. The tapered porous polyvinylidene fluoride tip is effective as a stylus or pick for areas with tight tolerances. The tip is attached to the handle without the use of potentially contaminating adhesives or glues. These swabs are ideal for adhesive and lubricant application.

- Polyvinylidene fluoride tip has low extractables and particulate levels
- Compatible with most solvents and adhesives
- Tapered 1.925 mm tip can be used as a stylus
- Assembled without adhesives or glues

COMPATIBILITY

Microtips™ Swabs are compatible with most common solvents such as alcohols, ketones, hydrocarbon and chlorinated solvents.

Chemtronics® is a registered trademark of Chemtronics. All rights reserved.
Microtips™ is a trademark of Chemtronics. All rights reserved

AVAILABILITY

Microtips™

CM502

50 swabs / bag

Total swab length: 6.7" (17 cm)
Tip: 0.07" x 0.62" (1.93 mm x 15.7 mm)
Handle Thickness: 0.13" (3.3 mm)

TECHNICAL AND APPLICATION ASSISTANCE

Chemtronics provides a technical hotline to answer your technical and application related questions.

The toll free number is: **1-800-TECH-401.**

CHEMTRONICS

8125 Cobb Center Drive

Kennesaw, GA 30152 USA

1-770-424-4888

REV. A (08/13)

DISTRIBUTED BY: