



## TG-996-3

# Ultra-Soft Silicone Thermal Pad

Version 2.130218

#### Ultra-Soft Silicone Thermal Pad

TG-996-3 is an ultra-soft, silicone thermal pad, suitable for use as thermal interface material or heat sink to dissipate the heat from electronic devices, especially in integrated circuit (IC) and LED packaging.

#### **Features**

Low thermal impedance, good surface compliance, high dielectric breakdown voltage, very low hardness and elasticity, high thermal conductivity, good high temperature resistance and good electrical insulation. Wide range of formats ranging from custom die cut parts to standard sheets in a range of thicknesses depending on the end application.

### **Applications**

Soft silicone based thermal interface material or heat sink to dissipate the heat from electronic devices, especially in integrated circuit (IC) devices and LED packaging.

## **Properties**

- ✓ REACH Compliant
- ✓ ROHS Compliant

Property	TG-996-3	Unit	Tolerance	Test Method
Binder	Silicone	-	-	-
Colour	White	-	-	Visual
Reinforcement	None	-	-	-
Specific gravity	2.2	-	-	-
Thermal Conductivity	2.2	Wm <sup>-1</sup> K <sup>-1</sup>	-	ASTM D5470
Hardness	35	Shore 00	-	ASTM D2240
Surface Tacky	Both sides tacky	-	-	-
Flammability	V-0	-	-	UL 94
Shelf Life	36	months	-	-
Shelf Life with adhesive (can be requalified for further 12)	12	months	-	-

#### Part Number Information

Product	Length	Width	Thickness	Adhesive
TG-996-3	288mm	192mm	0.5-2.0mm	Option available

#### Storage

Store this silicone thermal pad in air tight container in a cool, dark place (temperature range from 20°C to 30°C) to prolong shelf life. Store in dry conditions.

T-Global Technology Limited 1 & 2 Cosford Business Park, Central Park, Lutterworth, Leicestershire LE17 4QU U.K.

Tel: +44 (0)1455 553 510

Email: sales@tglobaltechnology.com Web: www.tglobaltechnology.com

Skype: tglobal.technology VAT #: GB 116 662 714

**NOTICE:** The information contained herein is to the best of our knowledge true and accurate. However, since the varied conditions of potential use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part and users should make their own test to determine the suitability of our products in any specific situation. This product is sold without warranty either expressed or implied, of fitness for a particular purpose or otherwise, except that this product shall be of standard quality, and except to the extent otherwise stated in T-Global Technology Europe and North America's invoice, quotation, or order acknowledgment. We disclaim any and all liabilities incurred in connection with the use of information contained herein, or otherwise. All risks of such are assumed by the user. Furthermore, nothing contained herein shall be construed as a recommendation to use any process or to manufacture or to use any product in conflict with existing or future patents covering any product or material or its use.