# **3M™ Water Contact Indicator Tape 5557NA**

## **Product Description**

3M<sup>™</sup> Water Contact Indicator Tape 5557NA is a 7.6 mil (193 micron) printable product that shows area specific, long lasting indication when contacted by water. When liquid containing water comes in contact with the product, the color rapidly changes from white to red.

#### **Features and Benefits**

#### **Film Top Layer**

- Printable by thermal transfer, flexographic, and screen printing methods
- Provides improved ink receptivity
- · Provides protection from soiling and moisture during handling

### **Paper Backing**

• Highly absorbent, transports water to show indications

#### **Total Construction**

- · Rotary die cuttable
- No adhesive

### **Product Construction**

3M™ Water Contact Indicator Tape 5557NA	
Backing	Paper
Top Film	Polyester
Adhesive	None
Color	White
Standard Roll Length	180 yards



## **Typical Physical Properties**

**Note:** The following technical information and data should be considered representative or typical only and should not be used for specification purposes.


Property	Value	ASTM Test Method
Tape Thickness:	7.6 mil (0.19304 mm)	D-3652
Humidity Resistance:*		




Control, t = 0 days



Control, t = 0 days Indicator w/1 drop  $H_2O$  for one minute at arrow.



7 days @ 55°C, 95% R.H.



7 days @  $55^{\circ}$ C, 95% R.H. indicated w/1 drop H<sub>2</sub>O for one minute at arrow.

### **General Information**

- · Maximum roll length depends upon width.
- Maximum roll width = 12 in. (304.8 mm).
- Temperature resistance is -40°C to 65°C for days or weeks and up to 121°C for minutes or hours.

## **Application Ideas**

- Use as a water contact indicator in handheld or portable electronic devices such as smart phones, tablets and phablets, laptop computers and keyboards, wearable electronic devices, gaming and MP3 players, two-way radios and cordless phones, digital and video cameras, Li-MH batteries and chargers.
- Other applications where positive indication of water or aqueous solution contact is desired.

<sup>\*</sup>Tape is applied to polycarbonate panel and hung vertically in heat/humidity chamber.

## 3M™ Water Contact Indicator Tape 5557NA

## **Key Attributes**

Features	Benefits
Film Top Layer	Printable by thermal transfer, flexographic, and screen printing methods. Can be used for identification.
	Top coated film for improved ink receptivity.
	Provides protection from soiling and moisture during handling. Indication remains after prolonged immersion.
Paper Backing	Highly absorbent, quickly transports water to show indications.  Does not falsely indicate water contact in high humidity environments.  Performance not degraded by past high humidity exposures.

## **Storage and Shelf Life**

The shelf life of 3M<sup>™</sup> Water Contact Indicator Tape 5557NA is 12 months from the manufacture date when stored in original cartons at 21°C (71°F) and 50% relative humidity.

## 3M™ Water Contact Indicator Tape 5557NA

### Regulatory

For regulatory information about this product, contact your 3M representative.

### **Technical Information**

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

### **Product Use**

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

### Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

## **Limitation of Liability**

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.





3M Center, Building 225-3S-06 St. Paul, MN 55144-1000 1-800-251-8634 phone 651-778-4244 fax www.3M.com/electronics

