

SilFORT* UVHC5000 clear coat

Product Description

SilFORT UVHC5000 is a clear, solvent-based, UV-curing coating for use on polycarbonate parts to help protect against abrasion, chemical damage and degradation caused by ultraviolet radiation and weathering. It is an excellent candidate to consider for use on headlamp lenses for forward lighting, exterior/interior trim and exterior/interior polycarbonate sheets. It complies with the ECE automotive forward lighting regulations and is AMECA listed for five years exposure in Florida and Arizona.

Key Features and Typical Benefits

- 5 year weatherability listing
- Improved resistance to microcracking
- Transparency
- Easy-to-clean properties
- High chemical resistance
- ECE and AMECA compliant
- Overspray can be recovered and re-used
- Application by spray, dip, roller and flow
- Adhesion to various plastics

Typical Physical Properties

Property	Unit	Typical Value
Physical Form	–	Liquid
Appearance	–	Yellow
Solids Content	% by weight	approx. 45

Kinematic Viscosity (at 25 °C)	cSt	approx. 10
Density (at 25 °C)	g/cm ³	approx. 1.01
Shelf Life(1)	Months	15

1. From date of manufacturing, in original unopened container.

Typical properties are average data and are not to be used as or to develop specifications.

Potential Applications

- Automotive Forward Headlight Lenses
- High Performance Sheets and Films

General Considerations for Use

Application Method	Spray, flow, dip, roller coating, ink jetting
Reducing Solvents	1-Methoxy-2-propanol (CAS#107-98-2) 2-Butanol (CAS#78-92-2) 2-Propanol (CAS#67-63-0) ⁽²⁾
Relative Humidity (application and ambient flash off)	Max. 65%
Room Temperature Flash Off	20 – 30 °C for 1 – 3 minutes
Pre-heating	1.5 to 6 minutes to reach 65 – 95 °C part surface temperature ^{(3),(4)}
Intermediate Cool Down	Optional
UV-Cure	3 – 12 J/cm ² UV-A (EIT Inc. Power Puck II Device) ^{(5),(6)}
Recommended Hardcoat Thickness ⁽⁷⁾	8 – 16 µm
Recommended Thickness of Interpenetrating Layer	>1 µm ⁽⁸⁾

(2) Other compatible solvents may be considered.

(3) Longer pre-heating times may be required when using convection heating instead of IR-heating.

(4) Modified, high heat resistant PC grades may require higher pre-heat temperatures.

- (5) Use of un-doped, medium pressure mercury arc lamps or microwave powered Hg lamps with > 80 W/cm power is recommended. Typical UV-irradiance is 0.2 to 0.6 W/cm². 0.25 W/cm² or higher may be required to achieve desired adhesion results after harsh humidity cycles.
- (6) For applications that mainly require chemical resistance against solvents such as ketones, SilFORT UVHC5000 clear coat may be cured at a lower UV-dosage (1.5 J/cm²).
- (7) Refractive Index $n = 1.5$.
- (8) Higher thickness up to 6 μm may further improve adhesion after harsh humidity cycles.

For best results in applying clear coat, filter the coating solution by combining a 5 μm pre-filter, followed by a 1 μm absolute gel-filter.

To help ensure adequate UV-cure, work with the UV-lamp supplier to select suitable UV-reflectors for the parts to be treated.

Do not expose product to any source of visible white light prior to UV-cure. To avoid exposure when white light is present, do not use semi-transparent pipework.

Packaging

Currently available in:

25 kg Steel Pail with PE liner 180 kg Steel Drum with PE liner 25 kg (Pail)

181,6 kg Drum

Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute the permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

Product Safety, Handling and Storage

Customers should review the latest Safety Data Sheet (SDS) and label for product safety information, safe handling instructions, personal protective equipment if necessary, emergency service contact information, and any special storage conditions required for safety. Momentive Performance Materials (MPM) maintains an around-the-clock emergency service for its products. SDS are available at www.momentive.com or, upon request, from any MPM representative. For product storage and handling procedures to maintain the product quality within our stated specifications, please review Certificates of Analysis, which are available in the Order

Center. Use of other materials in conjunction with MPM products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

Limitations

Customers must evaluate Momentive Performance Materials products and make their own determination as to fitness of use in their particular applications.

25 kg Steel Pail with PE liner 180 kg Steel Drum with PE liner 25 kg (Pail)

181,6 kg Drum

Contact Information

Email

commercial.services@momentive.com

Telephone

Americas

+1 800 295 2392

Toll free*

+704 805 6946

Direct Number

*All American countries

Latin America

Brazil

+55 11 4534 9650

Direct Number

Mexico

+52 55 2169 7670

Direct Number

EMEAI- Europe, Middle East, Africa & India

Europe

+390510924300

Direct number

India, Middle East & Africa

+ 91 44 71212207

Direct number*

*All Middle Eastern countries, Africa, India,

ASIA PACIFIC

China

800 820 0202

Toll free

+86 21 3860 4892

Direct number

Japan

+81 3 5544 3111

Direct number

Korea

+82 2 6201 4600

For literature and technical assistance, visit our website at: www.momentive.com

DISCLAIMER:

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY “SUPPLIER”), ARE SOLD SUBJECT TO SUPPLIER’S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER’S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier’s materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier’s products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier’s standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

*SilFORT is a trademark of Momentive Performance Materials Inc.

The use of the “™” symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies. Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.