

VieTape AM9002

LABEL

DESCRIPTION

Vietape AM9002 Includes acrylic-based adhesive and polypropylene backing: features very good initial tack and adhesion properties on a wide range of substrates, including low surface energy substrates like HDPE or PP. , steel...

APPLICATION

The product is suitable for labelling of quality products such as cosmetics, toiletries, luxury articles, promotional labeling, automotive lubricants and household chemicals where durability and resistance to moisture or chemicals are required. This product is ideal for applications requiring 'substrate identical labeling' on polypropylene containers and in environmentally sensitive markets requiring recycling of 'polyolefin' packs.

STRUCTURE



PERFORMANCE FEATURES

Physical Properties	Values
FACESTOCK	
Color	Glossy transparent
Chemical based	Polypropylene film
Basic Weight	46 ± 3g/m ²
Thickness	54 ± 3µm
ADHESIVE	
Adhesive based	Emulsion acrylic

Issue date: September 2022

VIETAPE MATERIAL TECHNOLOGY CO., LTD

18F Tang Nhon Phu Street, Phuoc Long B District,
 Thu Duc City, Ho Chi Minh City, Vietnam

info@vietape.com
 (+84) 869 681639

www.vietape.com



VieTape AM9002

LABEL

Physical Properties	Values
LINER	
Based	High-density glassine paper
Basic Weight	57± 5g/m ²
Thickness	51 ± 5µm
TYPICAL PERFORMANCE DATA	
Total thickness	120± 10µm
Initial tack	16N/25mm
Adhesion (peel off 90°)	8.7N/25mm
Working temperature	- 20°C to 80°C

SHELF LIFE

12 months from date of manufacture when stored at 21°C (69°F) and 50% relative humidity.

The above values are sample observed values, not the guarantee performance.

Issue date: September 2022

VIETAPE MATERIAL TECHNOLOGY CO.,LTD

18F Tang Nhon Phu Street, Phuoc Long B District,
 Thu Duc City, Ho Chi Minh City, Vietnam

info@vietape.com
 (+84) 869 681639

www.vietape.com

